

RPM	VEEM PROPS AFTER REMOVAL OF 1/8" x 2 Diameter									FUEL	
	8/1/2021									BURN	NMPG
RPM	KTS	PORT	STBD	AVG	PORT	STBD	PORT	STBD	INCREASE	INCREASE	DIFF
2600	13.8	5.9	5.5	1.21	6.0	6.0	-	-			
2700	14.7	6.5	5.8	1.19	8.0	8.0			0.85	0.9	2%
2800	15.5	6.7	6.4	1.18	10.0	10.0	475.0	550.0	0.85	0.8	1%
2900	16.7	7.3	7.1	1.16	11.0	11.0	475.0	575.0	1.20	1.3	2%
3000	17.6	7.5	7.5	1.17	12.0	12.0	500.0	575.0	0.90	0.6	-1%
3100	18.6	8.4	7.8	1.15	13.5	13.5	510.0	600.0	1.00	1.2	3%
3200	19.8	8.7	8.4	1.16	15.0	15.0	525.0	600.0	1.20	0.9	-1%
3300	20.6	9.1	9.0	1.14	16.0	16.0	535.0	615.0	0.80	1.0	2%
3400	21.9	10.0	9.6	1.12	18.0	18.0	535.0	610.0	1.30	1.5	2%
3500	22.8	10.6	10.5	1.08	20.0	20.0	550.0	620.0	0.90	1.5	4%
3600	23.7	11.4	11.5	1.03	22.0	22.0	575.0	675.0	0.90	1.8	5%
3700	24.8	12.7	12.5	0.98	26.0	25.5	600.0	700.0	1.10	2.3	5%
3800	25.6	14.0	13.9	0.92	28.0	28.0	625.0	725.0	0.80	2.7	7%
WOT	26.6	14.8	14.6	0.90	29.0	28.0	700.0	790.0	1.00	1.5	1%
WOT	-	-	-								

WOT port = 3916 stbd = 3880 not averages, but max RPM achieved